

CS-CV206-B0-31WFR

720P indoor Internet Wi-Fi Camera



Introduction

EZVIZ products have been designed for your entertainment, communication, security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ you can talk to your loved ones, watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends, prevent household accidents.

Main Features



HD 720p



Support Micro SD card slot, up to 64GB



Support 2.4GHz Wi-Fi
(IEEE802.11b, 802.11g, 802.11n)



Two-way audio



True Day/Night, auto switch,
Infra-Red support up to 16ft
(5 meters)



Secure cloud recording* (Optional)

Dimension



Accessories (Reference)



Power Adapter



Quick Start Guide



Foam Sticker



Metal Plate



USB Cable

Specifications

| | |
|------------------------------|---|
| Model | CS-CV206-B0-31WFR |
| Camera | |
| Image sensor | 1/4" 1MP HD Progressive Scan CMOS |
| Shutter Speed | Self-adaptive shutter |
| Lens | 2.8mm@ F2.5, view angle:92° (Horizontal), 111°(Diagonal) |
| Lens Mount | M12 |
| Day & Night | IR cut filter with auto switch |
| DNR | 3D DNR |
| WDR | Digital WDR |
| Compression | |
| Video Compression | H.264 |
| H.264 Type | Main Profile |
| Video Bit Rate | HD; balance; and fluency. Adaptive bit rate. |
| Audio Compression | AAC |
| Audio Bit Rate | Self-Adaptive |
| Image | |
| Max. Resolution | 1280 × 720 |
| Frame Rate | Self-Adaptive Max: 25fps |
| Image setting | Brightness, contrast, saturation, etc. (configure via EZVIZ studio) |
| BLC | Support |
| Network | |
| Storage | Support Micro SD card (Max. 64G) |
| Smart Alarm | Motion detection |
| One-key configuration | SmartConfig (Wi-Fi One Push Configuration) |
| Protocols | Ezviz cloud proprietary protocol |
| Interface Protocol | Ezviz cloud proprietary protocol |
| General Function | Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Watermark |
| Wi-Fi | |
| Standard | IEEE802.11b, 802.11g, 802.11n Draft |
| Frequency Range | 2.4 GHz ~ 2.4835 GHz |
| Channel Bandwidth | Support 20/40MHz |
| Security | 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK |
| Transmission Rate | 11b: 11Mbps,11g :54Mbps,11n :150Mbps |
| General | |
| Operating Conditions | -4°F to 122 °F (-20°C ~ 50°C), Humidity 95% or less (non-condensing) |
| Power Supply | DC 5V±10% |
| Power Consumption | MAX. 3W |
| IR Range | MAX. 5 meters |
| Dimensions (mm) | 0.42ft x 0.19ft x 0.12ft (128mm x 58mm x 38mm) |
| Weight | 0.265 lb (120g) |