

SPECIFICATIONS



CAMERA

Image sensor	3 megapixel 1/2.8"Progressive Scan CMOS
Minimum illumination	0.01Lux @(F2.2,AGC ON) ,0 Lux with IR
Shutter	Self-adaptive shutter
Lens	1.2mm@ F2.2, Horizontal angle : 180° Diagonal angle : 180°
Lens Mount	M12
Day & Night	IR cut filter
DNR	3D DNR
WDR	Progressive WDR

COMPRESSION

Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	HD; balance; and fluency. Adaptive bit rate

IMAGE

Max. Resolution	1344 × 1344
Frame Rate	50Hz/60Hz: 15 fps (1344 × 1344)
Image setting	Brightness, contrast, saturation, etc. (configure via Ezviz studio)
BLC	Support

NETWORK

Storage	Support Micro SD card (Max. 128G)
Smart Alarm	Motion detection
One-key configuration	Wi-Fi configuration via QR code
Protocols	Ezviz cloud proprietary protocol
Interface Protocol	Ezviz cloud proprietary protocol
General Function	Flicker filter, dual-stream, heartbeat, mirror image, password protection

WIRELESS PARAMETERS

Standard	IEEE802.11a/b/g/n/ac
Frequency Range	2.412GHz ~ 2.462GHz/5.15GHz ~ 5.35GHz/5.725GHz ~ 5.825GHz
Channel Bandwidth	Support 20/40/80MHz
Security	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :135Mbps

GENERAL

Operating Conditions	-10° to 45°, Humidity 95% or less (non-condensing)
Power Supply	DC 5V±5%
Power Consumption	8W MAX
IR Range	7.5 meters
Dimensions (mm)	70 × 70 × 70,6mm
Weight	222g

What's in the box?

- 1x Mini Pano
- 1x Base
- 1x Power Cable
- 1x Quick Start Guide
- 1x Screw Kit
- 1x Power Adapter
- 1x Base Cover
- 1x Drill Template