

# SPECIFICATIONS



## CAMERA

<b>Image sensor</b>	3 megapixel 1/2.8" Progressive Scan CMOS
<b>Minimum illumination</b>	0.01Lux @(F2.2,AGC ON), 0 Lux with IR
<b>Shutter</b>	Self-adaptive shutter
<b>Lens</b>	1.2mm@ F2.2, Horizontal angle : 180° Diagonal angle : 180°
<b>Lens Mount</b>	M12
<b>Day &amp; Night</b>	IR cut filter
<b>DNR</b>	3D DNR
<b>WDR</b>	Progressive WDR

## COMPRESSION

<b>Video Compression</b>	H.264
<b>H.264 Type</b>	Main Profile
<b>Video Bit Rate</b>	HD; balance; and fluency. Adaptive bit rate

## IMAGE

<b>Max. Resolution</b>	1344 × 1344
<b>Frame Rate</b>	50Hz/60Hz: 15 fps (1344 × 1344)
<b>Image setting</b>	Brightness, contrast, saturation, etc. (configure via Ezviz studio)
<b>BLC</b>	Support

## NETWORK

<b>Storage</b>	Support Micro SD card (Max. 128G)
<b>Smart Alarm</b>	Motion detection
<b>One-key configuration</b>	Wi-Fi configuration via QR code
<b>Protocols</b>	Ezviz cloud proprietary protocol
<b>Interface Protocol</b>	Ezviz cloud proprietary protocol
<b>General Function</b>	Flicker filter, dual-stream, heartbeat, mirror image, password protection

## WIRELESS PARAMETERS

<b>Standard</b>	IEEE802.11a/b/g/n/ac
<b>Frequency Range</b>	2.412GHz ~ 2.462GHz/5.15GHz ~ 5.35GHz/5.725GHz ~ 5.825GHz
<b>Channel Bandwidth</b>	Support 20/40/80MHz
<b>Security</b>	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
<b>Transmission Rate</b>	11b: 11Mbps, 11g: 54Mbps, 11n: 135Mbps

## GENERAL

<b>Operating Conditions</b>	-10° to 45°, Humidity 95% or less (non-condensing)
<b>Power Supply</b>	DC 5V±5%
<b>Power Consumption</b>	8W MAX
<b>IR Range</b>	7.5 meters
<b>Dimensions (mm)</b>	70 × 70 × 70,6mm
<b>Weight</b>	222g

### What's in the box?

- 1x Mini Pano
- 1x Base
- 1x Power Cable
- 1x Quick Start Guide
- 1x Screw Kit
- 1x Power Adapter
- 1x Base Cover
- 1x Drill Template